

COMPACT TRACK LOADER T450

Operating Weight 2914 kg 41.0 kW **Engine Power Rated Operating Capacity** 707 kg



One Tough Animal

T450 T4 - SPECIFICATIONS

Performance		Dimensions				
Rated operating capacity (ISO 14397-1) Tipping load (ISO 14397-1) Pump capacity Pump capacity (with high flow-option) System relief at quick couplers Max. travel speed Max. travel speed (high range-option)	707 kg 2019 kg 63.2 L/min - 22.4-23.1 MPa 11.7 km/h 17.7 km/h			K		
Engine		7	Com	1		
Make/Model Fuel Cooling	Bobcat/2.4L Engine (T4) Diesel Liquid	ļ, ţ		H H		
Power at 2400 RPM (SAE J1995 Gross) Torque at 1600 RPM (SAE J1995 Gross) Number of cylinders Displacement Fuel tank	41.0 kW (55.0 HP) 204.0 Nm 4 2393 cm ³ 64.9 L	(A) (B) (C) (D) (E)	3604.0 mm 1976.0 mm 28.0° 213.0 mm 1275.0 mm	(J) (K) (L) (M) (N)	2781.0 mm 597.0 mm 40.0° 91.0° 1422.0 mm	
Weights		(F)	2499.0 mm	(0)	1979.0 mm	
Operating weight Shipping weight without bucket	2914 kg 2598 kg	(G) (H) (I)	3216.0 mm 26.0° 2129.0 mm	(P) (Q)	1097.0 mm 1397.0 mm	
Controls						
Vehicle steering Loader hydraulics tilt and lift	Direction and speed controlled by two hand levers or joysticks (optional) Separate foot pedals or Selectable Joystick Controls (SJC)	Attachments Angle broom Augers Backhoes Brush saw Brushcat™ rotary cutter Bucket, construction Bucket, low profile Bucket, snow		Plar	Pallet forks, hydraulic Planer Salt & sand spreader Scraper Snow blade Snow V-blade Snowblower Sod layer	
Front auxiliary (standard) Drive System	Electrical switch on right-hand steering lever			Scra		
Transmission Standard Features	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors			Sno Sno Sod		
Cushion suspension seat	Lift arm support	Combination bucket			Soil conditioner	
Automatically activated intake air heater	Work lights, front and rear		crete pump		pilizers, rear	
Auxiliary hydraulics: variable flow/maximum flow Bob-Tach™ frame Bobcat Interlock Control System (BICS)	Parking brake Seat belt Seat bar	Doze Dum	Digger Dozer blade Dumping hopper Grader		Sweeper Tiller Tilt-tatch Trench compactor	
Turbo-charger with approved spark arrestor Tracks-rubber Instrumentation	Deluxe operator cab ¹ Includes interior cab foam, side, top and rear windows, deluxe wire harness, dome light, electrical power port, cup holder, storage place and front door with windshield wiper	Grap	ple, farm/utility ple industrial aulic breaker	Utili	ncher ty frame ratory roller	
1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 an SAE-J1043 and ISO 3449, Level I	d ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of	Land	Iplane Iscape rake	Wat	er kit od chipper	
Options		Palle	et forks			
Deluxe instrument panel	Selectable Joystick Controls (SJC) Air ride seat with 3 point seat belt					
Power Bob-Tach™						
Cab analogura with hoating						
Cab enclosure with heating Air conditioning	Back-up alarm Beacon					



Bobcat is a Doosan company. Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering proudly serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2023 Bobcat Company. All rights reserved.



Doosan Bobcat Korea Co., Ltd. www.bobcat.com